

Serial No. 10/600,096  
Docket No. 146712010300

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : 07-310739

(43)Date of publication of application : 28.11.1995

(51)Int.Cl.

F16C 17/10

(21)Application number : 06-126983

(71)Applicant : SANKYO SEIKI MFG CO LTD

(22)Date of filing : 17.05.1994

(72)Inventor : NOSE TAMOTSU  
KANEBAKO HIDEKI

## (54) DYNAMIC PRESSURE BEARING DEVICE

### (57)Abstract:

PURPOSE: To dimensionally control a stable runout characteristic in a thrust direction with a small shaft loss and without any need of much stringency.

CONSTITUTION: This device is provided with a fixed member 1 having a recess with one end closed and the other end open, a rotating shaft 3 inserted in the recess of the member 1, a thrust bearing to support the shaft 3 in a thrust direction and form the bottom section 1b of the recess, and radial bearings 2 and 2 to support the shaft 3 in a radial direction. Each bearing is filled with a non-compressive fluid 14 at the slide surface. Also, a large diameter section 23 having an outer diameter  $r_2$  larger than the diameter  $r_3$  of the slide surface of the radial bearings 2 is formed at a position inside the bearings 2a along the radial direction of the shaft 3. Furthermore, a small gap section A is formed between the section 23 and a fixed member 1a faced thereto, and space 25 for housing the section 23 is filled with the fluid 14.

